

## SYNPro 60

Stunning realism at a budget-friendly value make this artificial grass a perfect fit for those seeking premium quality at a economical price.

SKU

Grass Zone Yarn/Color

**Grass Zone Denier** 

Thatch Zone Yarn/Color

**Thatch Zone Denier** 

Grass Zone Yarn Shape

Finished Pile Height

Finished Pile Weight

Backing

**Tuft Gauge** 

**Total Weight** 

**Tuft Bind** 

Permeability

**Features** 

**Test Data** 

SYN60

PE / Field Green / Apple

10,800 / 6

PE / Field Green / Beige

5,000/8

Omega / 'S' Shape

1 1/2"

60 oz.

15 / 18 PP 2-Part / 22oz. EnviroLoc™

3/8"

88 oz.

> 8 lbs.

> 300 inches per / SY

EnviroLoc™, HeatBlock™, Deluster, **UV Stabilizers** 

ASTM Certified F1292, F1551, F1951

**Unmatched Lifetime Warranty** 



EnviroLoc™ Plant-Based Backing



Deluster + UV Protection



RECOMMENDED USES























Primary Yarn Polymer	Polyethylene
Yarn Cross Section	Omega / 'S' Shape
Standard Color	Field Green / Apple
Fabric Construction	Tufted
Second Yarn Polymer Thatch	Polyethylene
Secondary Yarn Color	Field Green / Beige

Primary Backing	15/18 PP 2-Part	
Coating Type	22 oz. EnviroLoc™	
PE Yarn Denier / Ends	10,800 / 6	
Texturized Thatch Denier / Ends	5,000 / 8	
Warranty Period	Limited Lifetime	

Finish Fabric	English	System	ASTM Test
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 1/2	inches	D-5823
Face Weight	60	oz/yd²	D-5848
Total Fabric Weight	88	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,800	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	344.31	in/hr	D-1551
Fabric Width	15	ft	-







