

PRODUCT SPECIFICATIONS





Designed with athletes in mind, SpeedTurf[™] by SYNLawn is a non-infill, low-friction turf with a foam backing pad that absorbs energy reducing the impact on the body.

SKU	SPEED					
Grass Zone Yarn/Color	PE / Field Green w/White Lines		9 Year Warra	anty		
Grass Zone Denier	8,000 / 1		Protection			
Thatch Zone Yarn/Color	Nylon / Green / White					
Thatch Zone Denier	4,200 / 8		Deluster			
Grass Zone Yarn Shape	Slit Film					
Finished Pile Height	3/4"					
Finished Pile Weight	60 oz.			0		Ser and a series of the series
Backing	15 / 18 PP 2-Part / 5mm Cushion	5m	4" White Stripe			19
Tuft Gauge	3/16"		Artificial Grass Fiber			
Total Weight	116 oz.	C Le	earn more at C	ADdetails.com		
Tuft Bind	> 8 lbs.	Nc	ot to scale. For illustra	ation only.		
Permeability						
Features	Deluster, UV Stabilizers	RECOMMENDE	D USES			
Test Data	ASTM Certified F1292, F1951	м	ULTI-SPORT -	- SPEED/TRACK -	AGILITY	





For ordering and questions, contact SYNLawn at 866-796-5296 or visit SYNLawn.com





f 💙 in 🖸 G+ 🞯

Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	Slit Film	Primary Backing	15/18 PP 2-Part
Standard Color	Field Green w/White Lines	Cushion	5mm Padding
Fabric Construction	Tufted	PE Yarn Denier / Ends	8,000 / 1
Second Yarn Polymer Thatch	Nylon	Texturized Thatch Denier / Ends	4,200 / 8
Secondary Yarn Color	Green / White	Warranty Period	9 Years

Finish Fabric	English	System	ASTM Test	
Nominal Specification	Value	Units	Method	
Pile Height (Nominal)	3/4	inches	D-5823	
Face Weight	60	oz/yd²	D-5848	
Total Fabric Weight	116	oz/yd²	D-5848	
Primary Backing Weight	6	oz/yd²	D-5848	
Secondary Coating Weight	50	oz/yd²	D-5848	
Tuft Bind	> 8	lbs.	D-1335	
Grab Tear Strength (Average)	> 200	lbs.	D-5034	
Total Yarn Linear Density	12,200	Denier	D-1577	
Elongation to Break	> 30	%	D-2256	
Yarn Breaking Strength	> 20	lbs.	D-5793	
Machine Guage	3/16	inches	D-5793	
Flammability	Passed	-	D-2859	
Water Permeability	-	in/hr	D-1551	
Fabric Width	15	ft		